



Single Nozzle CNG Portable Gas Dispenser 5 To 50L/Min Natural Gas Pump

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Virette
- Certification: GB/T 3836.1-2021
- Model Number: D1
- Minimum Order Quantity: 1 set
- Price: 1500USD-8000USD
- Delivery Time: 25 work days
- Payment Terms: T/T, Western Union
- Supply Ability: 30 set per month



Product Specification

- Product: CNG Gas Dispenser
- Size: 120×690×2100 (1 Hose/2 Hoses) (mm)
- Accuracy: ±0.3
- Frequency: 50HZ±1HZ/60HZ±1HZ
- Flow Range: 5 To 50L/min/9 To 90L/min
- Rated Power: 0.75KW
- Measurable Minimum: 5L/9L
- Noise: ≤80dB(A)
- Ambient Temperature: -40 To+60
- Nlet Vacuum: ≥0.06MPa
- OEM: Yes
- Warranty: 1 Year
- Highlight: CNG Portable Gas Dispenser,
Single Nozzle Portable Gas Dispenser,
50L/Min Natural Gas Pump

for more products please visit us on refueling-equipment.com

Product Description

China Manufacturers Gas Station Single Nozzle CNG Gas Dispenser

Product	CNG Gas Dispenser
Size	120×690×2100 (1 hose/2 hoses) (mm)
Accuracy	±0.3
Rated power	0.75KW
Flow range	5 to 50L/min/9 to 90L/min
Measurable Minimum	5L/9L
Noise	≤80dB(A)
Ambient Temperature	-40 to+60

Single-line CNG dispenser applications are used in gas filling stations with a constant pressure of about 20MPa.

Two-line CNG dispenser applications are used in gas stations with only two changes low pressure and high pressure. When refilling the car, first low-pressure inflation and then high-pressure inflation.

The three-line CNG dispenser has three air inlets, which are respectively connected to high-pressure, medium-pressure, and low-pressure gas storage tanks. When starting the gas filling, open the low-pressure valve first, and use the low-pressure storage tank to fill the gas. When the flow rate is less than the low-pressure-medium-pressure switching flow rate, open the medium-pressure valve, and use a medium-pressure storage tank for refueling. When the flow rate is less than the medium-high-pressure switching flow rate, open the high-pressure valve and use the high-pressure storage tank for refueling. When the flow rate is less than the minimum set flow rate, it will shut down and end the refueling.

>Ambient Temperature: -40°C~+55°C

>Ambient humidity: 30%~90%

>Power: AC220V+20%

>Flow rate:(1%30) kg/min

>Measurement precision:±0.5%

>Working pressure: <25MPa

>Density preset range: 0.5000-0.9999

>Unit price range: 0~9999

>Single range:19900.00

>Accumulative range: 09999999999.99

>Electronic Calibration.

>Printer (option).

xFueling times limit function.

Stop fueling by integer sale

>Can set the decimal point for the display, so can be used in many countries with different currency rates.

Leaves the communication ports, so it can communicate with the gas station management system.

xCan communicate with the IC card reader



Virette Technology Co., Ltd.

+8615651807973

ryan.s@youngtionech.com

refueling-equipment.com

Shizishu Industrial Concentration Zone, GuxiongStreet, Yuhuatai District, Nanjing City, Jiangsu Province, China